

Article No.	CT 483	CT 482	CT 481	CT 484	CT 488	CT 485	CT 486	CT 487
<i>Properties</i>								
Grain size [mm]	0.06 - 0.36	0.20 - 0.80	0.35 - 1.50	0.18 - 0.50	0.4 - 0.8	0.7 - 1.2	1.0 - 2.0	2.0 - 3.0
Grain size [mm]	0.063	0.200	0.355	0.180	0.400	0.700	1.000	2.000
Grain size [mm]	0.355	0.800	1.500	0.500	0.800	1.250	2.000	3.150
Color	Sand-colored, grayish				Sand-colored, reddish			
Packaging	Paper bag				PE bag			
<i>Use</i>								
Grain size [mm]	0.06 - 0.36	0.20 - 0.80	0.35 - 1.50	0.18 - 0.50	0.4 - 0.8	0.7 - 1.2	1.0 - 2.0	2.0 - 3.0
Characterization	Broader grading curve for universal applications				Narrower grading curve for special applications			
Typical fields of application	Universal filling sand	Mortar mixtures			Dispersion			Drainage screed
<i>Use</i>								
Grain size [mm]	0.06 - 0.36	0.20 - 0.80	0.35 - 1.50	0.18 - 0.50	0.4 - 0.8	0.7 - 1.2	1.0 - 2.0	2.0 - 3.0
For mixtures with concrete	✓	✓	✓	✓	✓	✓	✓	✓
For mixtures with epoxy resins	✓	✓	✓	✓	✓	✓	✓	✓
<i>KÖSTER related products</i>								
Grain size [mm]	0.06 - 0.36	0.20 - 0.80	0.35 - 1.50	0.18 - 0.50	0.4 - 0.8	0.7 - 1.2	1.0 - 2.0	2.0 - 3.0
KÖSTER LF-BM	✓		✓		✓	✓	✓	✓
KÖSTER Construction Resin	✓		✓		✓	✓	✓	✓
KÖSTER CT 121	✓ OS 8 System		✓		✓			
KÖSTER CT 221	✓				✓ OS 8 System			
KÖSTER LF-VL	✓	✓		✓	✓	✓	✓	
KÖSTER PS Flex	✓							
KÖSTER SL		✓						
KÖSTER SL Protect						✓	✓	

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.